

RUST RECONVERTER

RUST CONVERTER & PROTECTIVE COATING / PRIMER

RUST RECONVERTER LT PRODUCT HIGHLIGHTS

Stops further corrosion or rust on any metal surface. Chemically converts rust into a black organic 'shell' with a clear acrylic coating. Coating itself is sufficient to last for years, but is an excellent primer for latex, epoxy and oil-based paints. Extends the life of anything made of metal.

SAFETY PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN.

Harmful if swallowed.

Store product in a sealed, properly-marked container when not in use.

Refer to MSDS for complete safety information prior to using this or any other chemical product.

DIRECTIONS

Shake well.

Clean surface of loose rust and scale with a wire brush or abrasive pad.

Apply product evenly at the rate of 300 to 500 sq. ft. per gallon.

Apply by brushing, dipping, swabbing or spraying. May be applied by any equipment designed to spray latex paint.

Product may be thinned, if necessary, by adding up to 3 ozs. of water per gallon.

Allow to dry completely.

Do not store product at 32° or below.



Dallas, TX • 800-638-7361 • corrosionx.com
All Products 100% Made in the USA

RUST RECONVERTER

RUST CONVERTER & PROTECTIVE COATING / PRIMER

RUST RECONVERTER LT PRODUCT HIGHLIGHTS

Stops further corrosion or rust on any metal surface. Chemically converts rust into a black organic 'shell' with a clear acrylic coating. Coating itself is sufficient to last for years, but is an excellent primer for latex, epoxy and oil-based paints. Extends the life of anything made of metal.

SAFETY PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN.

Harmful if swallowed.

Store product in a sealed, properly-marked container when not in use.

Refer to MSDS for complete safety information prior to using this or any other chemical product.

DIRECTIONS

Shake well.

Clean surface of loose rust and scale with a wire brush or abrasive pad.

Apply product evenly at the rate of 300 to 500 sq. ft. per gallon.

Apply by brushing, dipping, swabbing or spraying. May be applied by any equipment designed to spray latex paint.

Product may be thinned, if necessary, by adding up to 3 ozs. of water per gallon.

Allow to dry completely.

Do not store product at 32° or below.



Dallas, TX • 800-638-7361 • corrosionx.com
All Products 100% Made in the USA